

Vapac[®]

Humidification and Steam Generation Specialists



Electrode Boiler

Comfort/Close Control Humidification Production

UK Distributor

HUMIDITY
SOLUTIONS
Independently better

 **NORTEK**[™]
GLOBAL HVAC



Electro Boiler

Comfort/Close Control Humidification Production

VapaNet Control System

The LE and LEP feature the VapaNet control system which is designed with user interaction in mind. It is easy for the user or engineer to gain instant information about the performance of the humidifier.

LE Comfort Control Model ($\pm 10\%$)

Incorporating an intelligent combination of feeding, boiling and draining to minimise wastage of water and energy. Water level control technology gives a performance turnaround of between 20% and 100% of designated unit performance.

LEP Close Control Model ($\pm 5\%$)

The unique Pulsed Energy control provides infinitely variable steam output from 8% up to 100% of full capacity.

Typically, the VapaNet Pulsed Energy (LEP) can be used in close tolerance applications.

Room Distribution Unit (RDU)

This is available for both LE and LEP models up to 45 Kg/hr and would be ideal for applications where AHU/ducts are unavailable.

They can be supplied either fixed to the humidifier or loose for remote mounting directly into the room.

Steam Output and Electrical Requirements

Model	Maximum Steam Output Kg/hr	Number of Cylinders / Steam Outlets	Diameter of Steam Outlets mm	Voltage V	Electrical Supply	Maximum Power Rating kW	Full Load Current Range (per phase) Amps	Maximum Fuse Rating Range (per phase) Amps
LE05*	5	1	35	200 / 440	Phase + N or 2 Phase	3.8	19.5 (9)	32 (16)
LE09*	9	1	35	200 / 440	Phase + N or 2 Phase	6.8	35.5 (16)	63 (25)
LE18	18	1	35	200 / 440	3 Phase	13.5 4	0.5 (18.5)	50 (32)
LE30†	30	1	54	200 / 440	3 Phase	22.5	68 (31)	80 (50)
LE45†	45	1	54	380 / 440	3 Phase	33.9	54 (46)	63
LE55	55	1	54	380 / 440	3 Phase	41.37	66 (57)	80
LE60†	60	2	54	380 / 440	3 Phase	45	71 (62)	2 x 50
LE90	90	2	54	380 / 440	3 Phase	67.8	108 (92)	2 x 63
LE110	110	2	54	380 / 440	3 Phase	41.37	66 (57)	2 x 80

*Also available in 3 Phase – Please contact Vapac for more information. †Low Voltage model available on request – Please contact Vapac for more information.

Features

- > Nine Capacities
5 - 110 Kg/hr steam generation.
- > Close Control and Comfort Control Versions
On/Off control (LE)
Water Level control 20 - 100% (LE)
Pulsed Energy control 8 - 100% (LEP)
- > Electrical Supply Options
200 - 440 volt, Phase + Neutral or 2 Phase, 3 Phase.
- > User Display
- > Control Network
- > Run and Alarm Interface
- > Master/Slave Option
VapaNet allows for a maximum of 10 cylinders to communicate within a Master/Slave system with an interconnecting two-core cable.
- > Foam Protection
- > Stainless Steel Drain Tray
- > Drain Pump
- > Control Features
The humidifier can be controlled directly from either a duct or room mounted sensor, supplied by Vapac or any other leading brand, or an external signal.
- > Disposable cylinders fitted as standard, cleanable cylinders available by request



Optional Accessories

- > Alpha-Numeric Display.
- > Communication Cable.
- > A full range of compatible accessories available on request.

Technical Data		
Operating Limits	Water Supply	Water and Drain Connections
Ambient Air Temperature‡ 5°C to 35°C Water Temperature‡ 1°C to 30°C Duct Pressure: +2000 to -600 Pa	Conductivity: 80 to 1000µs Ph: 7.3 to 8.0 Supply Pressure: 1 to 8 bar Silica: 0 Hardness: 50 to 500 ppm	Supply Water: ¾" BSP Drain Outlet: 35mm OD

‡Without frost protection.

Steam Output and Electrical Requirements								
Model	Maximum Steam Output Kg/hr	Number of Cylinders / Steam Outlets	Diameter of Steam Outlets mm	Voltage V	Electrical Supply	Maximum Power Rating kW	Full Load Current Range (per phase) Amps	Maximum Fuse Rating Range (per phase) Amps
LE05P	5	1	35	200 / 440	Phase + N or 2 Phase	3.8	23 (11)	32 (16)
LE09P	9	1	35	200 / 440	Phase + N or 2 Phase	6.8	41 (19)	63 (25)
LE18P	18	1	35	200 / 440	3 Phase	13.6	47 (22)	50 (32)
LE30P	30	1	54	200 / 440	3 Phase	22.5	78 (36)	100 (50)
LE45P	45	1	54	380 / 440	3 Phase	34	62 (53)	80
LE60P†	60	2	54	380 / 440	3 Phase	45	82 (72)	2 × 50
LE90P	90	2	54	380 / 440	3 Phase	67.8	124 (106)	2 × 80

See installation and operational manual for full electrical specification. †Low Voltage model available on request – Please contact Vapac for more information.

Dimensions and Weights

Cabinet Model	LE05 LE05P	LE09 LE09P	LE18 LE18P	LE30 LE30P	LE45 LE45P	LE55 –	LE60 LE60P	LE90 LE90P	LE110 –
Number of Cylinders	1	1	1	1	1	1	2	2	2
Height mm	676	676	676	810	810	810	810	810	810
Width mm	430	430	430	520	520	520	990	990	990
Depth mm	320	320	320	415	415	415	415	415	415
Dry Weight Kg	34	36	39	40	40	40	74	75	75
Wet Weight Kg	48	50	66	67	67	67	127	128	128
Room Distribution Unit (Fitted)									
Height mm	205	205	205	205	230	–	–	–	–
Width mm	430	430	430	602	842	–	–	–	–
Depth mm	265	265	265	360	360	–	–	–	–
Dry Weight Kg	6	10	12	14	16	–	–	–	–

UK Distributor

HUMIDITY SOLUTIONS LTD

Humidity House
1140a Axis
Cleeve Road
Leatherhead
Surrey
KT22 7ND

Tel: 01372 571200

E-mail: info@humiditiesolutions.co.uk

HUMIDITY
SOLUTIONS
Independently better

61/LE05/03/19
XXXXXXXXXXXX



Registered in England No. 01390934 | Registered Office The Colmore Building, Colmore Circus Queensway Birmingham B4 6A

Nortek Global HVAC is a registered trademark of Nortek Global HVAC Limited. Because of continuous product innovation, Nortek Global HVAC reserves the right to change product specification without due notice.

NORTEK GLOBAL HVAC (UK) LTD
Fens Pool Avenue
Brierley Hill
West Midlands DY5 1QA
United Kingdom

Tel: +44 (0)1384 489 250
Fax: +44 (0)1384 489 707

vapacsales@nortek.com
www.nortek.com